




10W MONOCRYSTALLINE SOLAR MODULE



FRONT VIEW



SIDE VIEW



BACK VIEW

ELECTRICAL CHARACTERISTICS

Power	10W		
Operating Voltage	18V	Open Circuit Voltage	21.6V
Operating Current	556mA	Short Circuit Current	610mA
Type of solar cell	Monocrystalline Silicon Solar Cell		
Power Tolerance	±5%		
STC: Irradiance 1000W/m ² , Module temperature: 25°C, AM=1.5			

TEMPERATURE COEFFICIENTS

Nominal Operating Cell Temperature (NOCT): 45°C±2°C	
Temp.Coefficient of Isc	(0.045±0.01)%/°C
Temp.Coefficient of Voc	-(0.34±0.01)/°C
Temp.Coefficient of Power	-(0.47±0.05)%/°C


TESTED OPERATING CONDITIONS

Max load	50psf 245kg/m ² (2400)pascals
Hailstone impact	25mm(1inch) at 23m/s(52mph)
Operating Temperature	-40° C to + 85° C

MECHANICAL SPECIFICATIONS

Dmensions	350×260×25mm
Encapsulation	Glass/EVA/Cells/EVA/TPT
Front Glass	Tempered Glass, thickness: 3.2mm
Frame	Anodized aluminum alloy (Silver)
Output lead wire	Without solder wire, with junction box
Dmension Tolerance: ±0.2mm Efficiency: ≥18%	

FIGURE OF STRUCTURE



WARRANTIES

Power output more than 90% for 10years
 Power output more than 80% for 25years
 Working life 25years

THE TECHNICAL FILES PROVIDED BY CHINA SOLAR LTD

Office Address:
 N0.401, ZhongKang Pioneer Park, ZhongKang Road,
 Futian District, ShenZhen City, Guangdong Province, China
 Factory Address:
 Longxi Hi-tech Industrial Park, Longcheng Road, Longgang
 Town, ShenZhen City, Guangdong Province, China