




## 2.8W 5V POLYCRYSTALLINE SOLAR MODULE



FRONT VIEW



SIDE VIEW



BACK VIEW

### ELECTRICAL CHARACTERISTICS

Power	2.8W		
Operating Voltage	5V	Open Circuit Voltage	6V
Operating Current	560mA	Short Circuit Current	616mA
Type of solar cell	Polycrystalline Silicon		
Power Tolerance	±5%		
STC: Irradiance 1000W/m <sup>2</sup> , Module temperature: 25°C, AM=1.5			

### TEMPERATURE COEFFICIENTS

Nominal Operating Cell Temperature (NOCT): 45°C±2°C	
Temp.Coefficient of Isc	(0.045±0.01)%/°C
Temp.Coefficient of Voc	-(0.34±0.01)%/°C
Temp.Coefficient of Power	-(0.47±0.05)%/°C


### TESTED OPERATING CONDITIONS

Max load	50psf 245kg/m <sup>2</sup> (2400)pascals
Hailstone impact	25mm(1inch) at 23m/s(52mph)
Operating Temperature	-40° C to + 85° C

### MECHANICAL SPECIFICATIONS

Dimensions	190×135×18mm
Encapsulation	Glass/EVA/Cells/EVA/TPT
Front Glass	Tempered Glass, thickness: 3.2mm
Frame	Anodized aluminum alloy (Silver)
Output lead wire	Without solder wire
Efficiency	≥15.8%

### FIGURE OF STRUCTURE



### WARRANTIES

Power output more than 90% for 10years  
 Power output more than 80% for 20years  
 Working life 20years

### THE TECHNICAL FILES PROVIDED BY CHINA SOLAR LTD

Office Address:

N0.401,ZhongKang Pioneer Park,ZhongKang Road,  
 Futian District, ShenZhen City,Guangdong Province,China

Factory Address:

Longxi Hi-tech Industrial Park, Longcheng Road, Longgang  
 Town, ShenZhen City,Guangdong Province,China